

StarOffice 3.1 Mini-HOWTO

Table of Contents

<u>StarOffice 3.1 Mini-HOWTO</u>	1
<u>Matthew Borowski (mkb@poboxes.com) (http://tarp.worldserve.net/)</u>	1
<u>1. Introduction</u>	1
<u>1.1 Motif info</u>	1
<u>1.2 History of this document</u>	2
<u>2. Obtaining the StarOffice Office Suite</u>	2
<u>3. Installation of StarOffice</u>	2
<u>3.1 Libc Issues and Fixes</u>	2
<u>3.2 Installing the tar Files</u>	3
<u>3.3 Setup und Configuration</u>	3
<u>3.4 COL (Caldera OpenLinux) setup bug</u>	4
<u>3.5 Fixing the LANG variable problem</u>	4
<u>4. Running StarOffice</u>	4
<u>5. StarOffice Tips</u>	5
<u>6. More Information</u>	5
<u>7. Contributions</u>	5
<u>8. Disclaimer and Copyright</u>	6

StarOffice 3.1 Mini-HOWTO

Matthew Borowski (mkb@poboxes.com)
(<http://tarp.worldserve.net/>)

v1.1, 28 November 1999

Information on installing the StarOffice 3.1 Office Suite by StarDivision.

1. Introduction

This document deals with installing StarOffice 3.1. The current version of StarOffice is 5.1. Version 5.1 is considerably easier to install and less buggy than version 3.1. In fact, in my opinion there is no need for a HOWTO for version 5.1, since StarDivision has written a fairly complete installation guide. The StarOffice mini-HOWTO was useful while it lasted, but it is now being archived only for the few who still wish to install StarOffice 3.1. For information about StarOffice 5.1, check StarDivision's site at <http://www.stardivision.com>.

The StarOffice Office Suite is a collection of office tools for Linux, written in C using the Motif toolkit.

StarOffice includes:

- StarWriter, a word processor
- StarCalc, a spreadsheet
- StarImage, an image editor
- StarDraw, a draw program similar to Corel DRAW
- StarChart, a chart-making program
- StarMath, a math editor

The StarOffice Office Suite for Linux is free for non-commercial use. Commercial use requires a license. The cost for a commercial license separate from Caldera's OpenLinux system is currently undecided.

1.1 Motif info

StarOffice is written using the commercial Motif 2.0 GUI toolkit. The dynamically linked version will **not** work with Motif 1.2/LessTif.

The static version (with Motif 2.0 linked in) will work regardless of whether or not you have Motif. However, performance drops.

I run StarOffice on a Pentium 100 with 48 megs RAM, running Redhat 4.1 and Motif 2.0. Dynamically linked StarOffice takes about a minute to load. However, it is noticeable that, once it loads up, StarOffice dynamically linked takes up much less resources than the static version.

1.2 History of this document

- Version 1.1 991128 - updated URLs and changed references to StarOffice 4.0 to the new 5.1
- Version 1.0 980602 - added information on StarOffice 4.0 and about how this document is now outdated
- Version 0.8 971109 - added tips, installation w/o libc upgrade, etc.
- Version 0.7 970707 - changed section 3.1.1, changed license
- Version 0.6 970609 - added fix for the LANG variable problem
- Version 0.5 970608 - updated info to StarOffice 3.1 final
- Version 0.1 970505 - the initial release.

2. Obtaining the StarOffice Office Suite

The release of StarOffice 3.1 for Linux is available for FTP at

<ftp://ftp.gwdg.de/pub/linux/staroffice>

The file `README.StarOffice` contains information on downloading StarOffice 3.1 final. You will need to get three files:

- `StarOffice31-english.tar.gz` (english) templates/demo docs or
- `StarOffice31-german.tar.gz` (german) templates/demo docs
- `StarOffice31-dynbin.tar.tgz` (dynamically linked) or
- `StarOffice31-statbin.tar.gz` (statically linked) binaries
- `StarOffice31-common.tar.gz`

There is also version of StarOffice, available from Caldera. Check their website at

<http://www.caldera.com>

for details on this. Caldera also makes a StarOffice CD-ROM available for \$ 7.99 US.

3. Installation of StarOffice

Installation of StarOffice consists of:

- Untarring the distribution files as root in `/usr/local`
- running the `setup` program as a user
- sourcing the `.sd.sh` or `.sd.csh`
- reading section 3.5!!! (do this)

3.1 Libc Issues and Fixes

StarOffice is linked with `libc 5.4.4`.

StarOffice 3.1 *will* work on `libc 5.3.x`. Unfortunately, the `setup` program requires 5.4.4 or higher. If you have `libc 5.3.x`, you might be able to get around this by acquiring a copy of `libc 5.4.4+` and adding it to your `LD_LIBRARY_PATH` environment variable before executing the `setup` script. I haven't tried this, however, so you're on your own.

StarOffice 3.1 Mini-HOWTO

If you attempt to run the `setup` script on a `libc` older than 5.4.4, you will get the following error message:

```
line 1: Syntax error at token 'I' expected declarator; i.e.  
File ...
```

To upgrade your `libc`, FTP to sunsite.unc.edu and look in the directory `/pub/Linux/GCC` for the file `libc-5.4.33.bin.tar.gz` (or whatever the latest `libc` is). Extract the contents of this file in a temporary directory. A new `lib/` directory will be created. Su to root and copy the file `libc.so.5.4.33` from this directory to your `/lib` directory. Now, make the symlink from `libc.so.5` to `libc.5.4.33` with the command:

```
ln -sf /lib/libc.so.5.4.33 /lib/libc.so.5
```

then run the `ldconfig` command.

Dr. Romano Giannetti (romano@iet.unipi.it) says:

...I want only to add that I could install (like you suggested) StarWriter in a redhat 4.2 system which has a `libc5.3`, without doing the upgrade.

The exact steps are:

1. get a `libc.so.5.4.x`. If you have a redhat rpm package (as the one you find in the contrib directory), you can extract the library by going in a scratch directory and doing: `rpm2cpio libc.so.5.4.x-y.rpm | cpio --extract --make-directories` The library will appear in `./lib` subdirectory
2. move `libc.so.5.4.x` in your home directory. Then (assuming a sh-like shell):

```
ln -s  
libc.so.5.4.x libc.so.5 export  
LD_LIBRARY_PATH=$HOME:/lib:/usr/lib
```
3. Now you can run `setup`.

3.2 Installing the tar Files

After downloading StarOffice, su or login as root and place the archives in `/usr/local/`. Change directory to `/usr/local/` and extract the files. An example command to decompress a gzipped tar file would be:

```
tar -xzvf filename.tar
```

Older systems may require you first use the `gzip -d` command to unzip the file, then use the `tar -xvf` command to untar it.

The files will extract to their locations within the newly created `usr/local/StarOffice-3.1` tree.

3.3 Setup und Configuration

After you have extracted the StarOffice files as root, you will need to login with your userid. Change directory to `/usr/local/StarOffice-3.1` and execute the `setup` program. This program will install non-shared files and symlinks needed for each individual user. The standard installation is recommended.

StarOffice 3.1 Mini-HOWTO

There *could* be problems if you do not accept the default installation path.

StarOffice makes use of environment variables. The files `.sd.sh` (formatted for the Bourne Shell) and `.sd.csh` (formatted for the C Shell) provide the environment variable settings for StarOffice. These files are located in your home directory.

If you use `bash`, edit your `.bashrc` and add the line:

```
source /sd.sh
```

After doing this, restart `bash` to bring the environment variables into effect.

If you use a different shell, consult that shell's man page for information on sourcing a file.

3.4 COL (Caldera OpenLinux) setup bug

Phil Reardon (pcr@busprod.com) says:

```
" I found a bug in the setup script for StarOffice that came with my Caldera COL standard release. It produces // in a path where there should only be one /. To fix it, remove the first slash from this line:
```

```
exec ${pfad:='./'}/linux-x86/bin/$name;;
```

```
There should be no / before linux-x86."
```

3.5 Fixing the LANG variable problem

The `.sd.sh` and `.sd.csh` files set the `LANG` variable. This causes problems with `perl` and `man`. `Man` will give the error message

```
" Failed to open the message catalog man on the path NLSPATH="
```

`Perl` will give the error message

```
" warning: setlocale(LC_CTYPE, "")..."
```

The `.sd.sh` file contains a line that sets `LANG=us` and another that exports a bunch of variables, including `LANG`. Remove the `LANG=us` line and remove `LANG` from the list of variables, and this will be fixed.

In the `.sd.csh` file (which is formatted for the `c` shell), you need to remove the line that says `"setenv LANG us"`.

Thanks to Adam L. Klein (alklein@adelphia.net) for informing me of this fix.

4. Running StarOffice

The StarOffice binaries are located in the directory:

```
/usr/local/StarOffice-3.1/linux-x86/bin/
```

StarOffice 3.1 Mini-HOWTO

The applications are: `sdraw3`, `swriter3`, `scal3`, `smath3`, `schart3`, `simage3`

The program `svdaemon` must be executed in order to use online help. The program `svportmap` must be executed to enable application communication features between StarWriter, StarCalc and StarDraw.

5. StarOffice Tips

Contributed by Patrick D'Cruze (pdcruze@netpal.com.au)

1. Instead of sourcing the `.sd.sh` (or `.sd.csh`) file in my `.bash_profile` script, I instead copied the `.sd.sh` script, renamed it to `swriter` and copied it to `/usr/local/bin`. I then modified it by adding a:

```
#!/bin/bash
```

at the start of the script and a:

```
exec swriter3 $*
```

at the end of the script. Now all I have to do is run `swriter` and it automatically sets up the appropriate environment variables and then runs StarWriter. Saves having those environment variables pollute other applications/environments.

2. I noticed that for a lot of people, StarOffice takes quite a while to load (upwards of 60 seconds). The consensus on usenet was that a large chunk of this time was due to the symbol relocations that the dynamic linker has to do. ie, for each new symbol the dynamic linker has to locate the appropriate library. StarOffice dynamically links against quite a few libraries so the dynamic linker spends quite a bit of time searching through lots of libraries.

There is a solution to this. I run StarOffice in a chroot'd jail. In the jail, I just put the binaries and libraries that StarOffice uses (all the libs out of `/usr/X11R6/lib`, `libc/libm` and `libg++/libstdc++`). StarWriter takes approximately 15 seconds to come up on my P133/32MB. This is due to the fact that the only libraries present are the ones needed by StarOffice and hence the dynamic linker spends proportionately less time searching through all the libraries on the system (ie, it doesn't search through all the useless libs in `/usr/lib` etc looking to resolve symbols).

6. More Information

More information on StarOffice for Linux is available directly from StarDivision. StarDivision maintains a website at <http://www.stardivision.com>

StarDivision runs a news server with support and user groups related to StarOffice for linux. These newsgroups are the best place to find up-to-date information on StarOffice and to ask for help. Using a newsreader, connect to <news://starnews.stardivision.com> or follow the support link on the StarDivision homepage.

7. Contributions

Thank you to Werner Klaus (wklaus@metronet.de) for translating this document to sgml.

If you can contribute any additional information for this mini-HOWTO, please contact me via internet e-mail. My address is located at the top of this document. You may also wish to take a look at my web page, located at <http://tarp.worldserve.net/> or <http://tarp.linuxos.org/>

8. Disclaimer and Copyright

This document is (C) 1999 by Matthew Borowski.

Redistribution of this document in electronic form is permitted under the condition that the document remains unchanged. If you wish to include this document in a CD-ROM or book, please obtain permission from me beforehand (I prefer requests to be sent via e-mail).

The author claims no responsibility in anything that may occur directly or indirectly as a result of using this document. The author is not an employee of StarDivision, GmbH or Caldera, Inc.

Comments and questions may be directed to the author at mkb@poboxes.com.